

The stainless steel finish AISI 304 guarantee an effective protection against the corrosion in critical environments. 4 adaptable feet to achieve a good level as well as a pit or pitless installation. Static overload stop in the load cell. 4 stops at the corner of the platform scale, which allow supporting higher overloads than the maximal capacity. Toll steels models with IP-67 protection degree, stainless steel models with IP-68 protection degree (depending on model and capacity) .All models with EC approval



#### CHARACTERISTICS

- Totally built in stainless steel with laser welding depending model with load cell IP68.
- Design that accomplishes all the hygienic standards according the CE regulations.
- Stainless steel AISI 316 manufacturing.

#### OPTIONS

- Atex version, 6.000 divisions, 15.000 divisions, 30.000 divisions, IP68

#### AVAILABLE VERSIONS

Model	Dimensions (cm)	Height (cm)	Capacity (kg)	Division (g)
MI15	15x15	5	3,6	1,2
MI20	20x20	5	3,6	1,2
MI25	25x25	5	3,6,15	1,2,5
MI30	30x30	5	3, 6, 15, 30	1, 2, 5, 10
MI40	40x40	10	3,6,15, 30, 60, 150	1,2,5, 10, 20, 50
MI50	40x50	10	3,6,15, 30, 60, 150	1, 2, 5, 10, 20, 50
MI45	45x60	12,5	30, 60, 150, 300	10, 20, 50, 100
MI60	60x60	12,5	30, 60, 150, 300	10, 20, 50, 100
MI80	80x80	15	150, 300, 600	50, 100, 200



Column Option



Rollers Option

**ISO** 9001

 Made in EUROPE